

# A93

## UNIVERSAL WC CISTERN ALCA UNI DUAL

### Application:

- For installation on plaster
- For mounting as high, medium and low-lying

### Features:

- The tank is isolated against condensation forming
- Water supply from left/right
- Universal brackets with their spacing and shape consistent with existing tanks
- Volume 8 l with a large variety of settings for the flushed volume of water
- Flushing DUAL 3/6 l
- Water saving setting
- Structural design ensures comfort when flushing even for children and people with disabilities

### Standards:

ČSN EN 14124, ČSN EN 14055

### Technical parameters:

Functional requirements	Class I
Big flush	6 – 8 l
Small flush	2.5 l
Default setting large flush	6 l
Default setting small flush	3 l
When installed in a high rise position the tank is functional only with the big flush	6 – 8 l
Acoustic group II	<30 dB
Working range	0.05 to 0.8 MPa
Recommended Operating Pressure	0.5 – 0.8 MPa

### Scope of supply:

- Tank:
- Filling and flushing valves
- Elbow Ø50/40 mm for the low-lying reservoir
- Flush set for the high-lying reservoir (cord, handle, lever)
- Flush set for low level tank installations (button small, large)
- Anchoring set: screw Ø5×40 – 2 pcs, anchor Ø8 – 2 pcs

### Logistic information:

Weight (piece)	2.8621 kg
Dimensions (piece)	456×142×410 mm
Quantity (packing)	1 pc
Quantity (pallet)	58 pcs

### Order number:

Code	EAN	Filling valve
A93-1/2"	8594045931051	1/2"
A93-3/8"	8595580501280	3/8"

