

SA08A-1/2"

FILL AND FLUSH KIT WITH DUAL CONTROL BUTTON

Application:

- For ceramic flushing cistern
- For replacement

Features:

- Plastic thread length 38 mm
- Built-in filter to trap dirt
- Smooth closing without any shocks
- Adjustable water level
- Low sensitivity to the difference in pressure in the water main
- The design allows optimum height adjustment of the valve according to the height of the tank
- DUAL flush mechanism 3/6 l
- Stop to adjust the amount of discharged water
- Option of the setting the button off the axis of the valve
- DUAL button chrome

Standards:

ČSN EN 14124, ČSN EN 14055

Technical parameters:

Height adjustment range	315 – 450 mm
Functional requirements	Class I
Flush volume of individual flushes is determined by the size and the volume of the tank	
Acoustic group II	<30 dB
Working range	0.05 to 0.8 MPa
Recommended Operating Pressure	0.5 – 0.8 MPa

Scope of supply:

- Inlet fill valve A15-1/2"
- Flush valve A08A
- Seal Kit
- Fixation set: M8x65 – 2 pcs
- Stopper chrome

Logistic information:

Weight (piece)	0.7062 kg
Dimensions (piece)	200x400x100 mm
Quantity (packing)	16 pcs
Quantity (pallet)	256 pcs

Order number:

Code	EAN
SA08A-1/2"	8595580532796

